

Fiberglass Solvent Wash 202

Thinners & Solvents

Removes Surface Contamination from Bare Fiberglass



PRODUCT DESCRIPTION

Interlux Fiberglass Solvent Wash 202 removes mold release agents, wax, oil and grease from hulls of bare fiberglass boats. It is also effective in removing wax and silicone contamination from painted hull surfaces that are being prepared for repainting with Interspray Finish Coatings. It is essential to use Fiberglass Solvent Wash 202 prior to painting fiberglass gel coats, regardless of their age. Fiberglass Solvent Wash 202 is, in addition, an effective brush cleaner.

PRODUCT INFORMATION

Colour	Y202
Specific Gravity	0.868
Volume Solids	0%
Typical Shelf Life	3 yrs
VOC (As Supplied)	868 g/lt
Unit Size	1 US Quart 1 US Gallon

DRYING/OVERCOATING INFORMATION

Drying

Overcoating

Substrate Temperature

Overcoated By	41°F (5°C)		50°F (10°C)		73°F (23°C)		95°F (35°C)	
	Min	Max	Min	Max	Min	Max	Min	Max

APPLICATION AND USE

Method	Wipe a small area with a clean rag that has been wetted with Fiberglass Solvent Wash 202. While the surface is still wet, wipe with a clean, dry rag. Continue this process until the entire surface has been cleaned. Rinse with fresh water. If water beads up or separates, wipe the surface again with Fiberglass Solvent Wash. When the water sheets off, all contamination has been removed. Do not paint until surface is clean and dry.
Some Important Points	Not for sale or use in California.
Compatibility/Substrates	For use on fiberglass gel coat to remove the residue, contamination and mold release agents.

TRANSPORTATION, STORAGE AND SAFETY INFORMATION


Storage	TRANSPORTATION: Fiberglass Solvent Wash 202 should be kept in securely closed containers during transport and storage. STORAGE: Exposure to air and extremes of temperature should be avoided. For the full shelf life of Fiberglass Solvent Wash 202 to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/40°F and 35°C/95°F. Keep out of direct sunlight.
----------------	--

Safety	DISPOSAL: Container Disposal: Triple Rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill or by other procedures approved by state or local authorities. GENERAL: Read the label safety section for Health and Safety Information, also available from our Technical Help Line.
---------------	---

IMPORTANT NOTES

The performance of any marine paint or coating depends on many factors outside the control of International Paint LLC., including surface preparation, proper application, and environmental conditions. Therefore, International Paint LLC. cannot guarantee this product's suitability for your particular purpose or application. IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND/OR MERCHANTABILITY ARE EXCEEDED. International Paint Inc. SHALL NOT, UNDER ANY CIRCUMSTANCES, BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. By purchase of this product, the buyer agrees that the sole exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at International Paint LLC. option.

Please refer to your local representative or visit www.yachtpaint.com for further information.

 Interlux®, the AkzoNobel logo and other products mentioned in this publication are trademarks of, or licensed to Akzo Nobel. ©Akzo Nobel 2009.

Ref:3019 Issue Date:10/13/2010

