

#### PRODUCT DESCRIPTION

Marine Polish is an ultra-fine grade polish with wax, for use on gelcoat and paintwork. Gives lasting protection and high gloss. For manual and machine polishing (800-1000 rpm). Free from silicone oils.

- \* Protects against saltwater, sunlight, oil etc.
- \* Polishes to a full gloss surface that is easy to clean
- \* Does not discolour scratches
- \* Also suitable for use on the car, caravan or garden furniture

#### PRODUCT INFORMATION

<b>Colour</b>	YMB833
<b>Specific Gravity</b>	1
<b>Volume Solids</b>	16%
<b>VOC (As Supplied)</b>	180 g/lt
<b>Unit Size</b>	500 ml

#### DRYING/OVERCOATING INFORMATION

##### Drying

##### Overcoating

##### Substrate Temperature

	5°C (41°F)		10°C (50°F)		23°C (73°F)		35°C (95°F)	
Overcoated By	Min	Max	Min	Max	Min	Max	Min	Max

#### APPLICATION AND USE

<b>Preparation</b>	Clean with Super Cleaner. Rinse with fresh water and allow to dry. For badly deteriorated surfaces use Liquid Rubbing first.
<b>Method</b>	Apply a thin layer of Marine Polish with a clean and dry cloth in a small area at a time. Allow to dry. Polish out to a high gloss, changing cloth frequently. Machine polishing (800-1000 rpm) is the most effective method. For maximum protection finish with Marine Wax or UV Wax Sealer.
<b>Hints</b>	Mixing - Shake well before use.
<b>Some Important Points</b>	Product temperature should be minimum 5°C/41°F and maximum 35°C/95°F. Ambient temperature should be minimum 5°C/41°F and maximum 35°C/95°F. Substrate temperature should be minimum 5°C/41°F and maximum 35°C/95°F.
<b>Compatibility/Substrates</b>	Suitable for use on GRP and painted surfaces.

#### TRANSPORTATION, STORAGE AND SAFETY INFORMATION

<b>Storage</b>	<p><b>GENERAL INFORMATION:</b> Exposure to air and extremes of temperature should be avoided. For the full shelf life of Marine Polish to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/41°F and 35°C/95°F. Keep out of direct sunlight.</p> <p><b>TRANSPORTATION:</b> Marine Polish should be kept in securely closed containers during transport and storage.</p>
<b>Safety</b>	<p><b>GENERAL:</b> Read the label safety section for Health and Safety Information, also available from our Technical Help Line.</p> <p><b>DISPOSAL:</b> Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to harden before disposal. Remainders of Marine Polish cannot be disposed of through the municipal waste route or dumped without permit. Disposal of remainders must be arranged for in consultation with the authorities.</p>
<b>IMPORTANT NOTES</b>	<p><i>The information given in this sheet is not intended to be exhaustive. Any person using the product without first making further written enquiries as to the suitability of the product for the intended purpose does so at their own risk and we can accept no responsibility for the performance of the product or for any loss or damage (other than death or personal injury resulting from negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.</i></p>

Please refer to your local representative or visit <http://www.yachtpaint.com> for further information.

All trademarks mentioned in this publication are owned by, or licensed to, the AkzoNobel group of companies. © AkzoNobel 2014.

