

Teak Restorer

Boatcare

Restoring and brightening hardwoods



PRODUCT DESCRIPTION

Teak Restorer cleans and restores teak and other hardwoods

- * Re-establishes the natural colour of teak
- * For use on any interior or exterior hardwood
- * For decks, teak details and finishing
- * Also suitable for garden furniture
- * Does not damage GRP, varnish, paintwork or aluminium
- * Biodegradable

PRODUCT INFORMATION

Colour	YMB840
Specific Gravity	0.99
Volume Solids	10%
Typical Shelf Life	2 yrs
VOC (As Supplied)	0 g/l
Unit Size	500 ml

DRYING/OVERCOATING INFORMATION

Drying

Overcoating

Substrate Temperature

	5°C (41°F)		10°C (50°F)		23°C (73°F)		35°C (95°F)	
Overcoated By	Min	Max	Min	Max	Min	Max	Min	Max

APPLICATION AND USE

Preparation	Wet out the teak thoroughly with fresh or salt water. If the teak is extremely dirty, clean surface with International Super Cleaner.
Method	Apply Teak Restorer generously and leave for 10-15 minutes. Scrub the surface across the grain. Repeat if required. Rinse with fresh water. For protection of the restored wood, treat with Teak Oil.
Hints	Mixing Shake well before use.
Some Important Points	Product temperature should be minimum 5°C/41°F and maximum 35°C/95°F. Ambient temperature should be minimum 5°C/41°F and maximum 35°C/95°F. Substrate temperature should be minimum 5°C/41°F and maximum 35°C/95°F.
Compatibility/Substrates	Suitable for use on teak and other hardwoods.
Application Methods	Cloth/Sponge

TRANSPORTATION, STORAGE AND SAFETY INFORMATION

Storage	GENERAL INFORMATION: Exposure to air and extremes of temperature should be avoided. For the full shelf life of Teak Restorer to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/41°F and 35°C/95°F. Keep out of direct sunlight. TRANSPORTATION: Teak Restorer should be kept in securely closed containers during transport and storage.
Safety	GENERAL: Read the label safety section for Health and Safety Information, also available from our Technical Help Line. DISPOSAL: Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to harden before disposal. Remainders of Teak Restorer cannot be disposed of through the municipal waste route or dumped without permit. Disposal of remainders must be arranged for in consultation with the authorities.
IMPORTANT NOTES	<i>The information given in this sheet is not intended to be exhaustive. Any person using the product without first making further written enquiries as to the suitability of the product for the intended purpose does so at their own risk and we can accept no responsibility for the performance of the product or for any loss or damage (other than death or personal</i>

Please refer to your local representative or visit <http://www.yachtpaint.com> for further information.

All trademarks mentioned in this publication are owned by, or licensed to, the AkzoNobel group of companies. © AkzoNobel 2014.

Teak Restorer

Boatcare

Restoring and brightening hardwoods



injury resulting from negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.

Please refer to your local representative or visit <http://www.yachtpaint.com> for further information.

All trademarks mentioned in this publication are owned by, or licensed to, the AkzoNobel group of companies. © AkzoNobel 2014.

Ref:3519 Teak Restorer Issue Date:15/12/2014