

# Y2002E\_A9

## Safety Data Sheet INTERPROTECT WHITE BASE



Bulk Sales Reference No.: Y2002E  
SDS Revision Date: 11/29/2021  
SDS Revision Number: A9-8

### 1. Identification of the preparation and company

#### 1.1. Product identifier

Product Identity INTERPROTECT WHITE BASE  
Bulk Sales Reference No. Y2002E

1.2. Relevant identified uses of the substance or mixture and uses advised against  
Intended Use See Technical Data Sheet.

#### 1.3. Details of the supplier of the safety data sheet

Company Name Akzo Nobel Coatings  
Manufacturer:  
Akzo Nobel Coatings  
International Paint  
6001 Antoine Drive  
Houston, Texas 77091

Emergency  
CHEMTREC (800) 424-9300  
International Paint (713) 527-3887  
Poison Control Center (800) 854-6813  
Customer Service  
International Paint (800) 589-1267  
Fax No. (800) 631-7481

### 2. Hazard identification of the product

#### 2.1. Classification of the substance or mixture

Flam. Liq. 3;H226 Flammable liquid and vapor.  
Skin Irrit. 2;H315 Causes skin irritation.  
Eye Dam. 1;H318 Causes serious eye damage.  
Skin Sens. 1;H317 May cause an allergic skin reaction.  
STOT RE 2;H373 May cause damage to organs through prolonged or repeated exposure.

#### 2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



Danger.

H226 Flammable liquid and vapor.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H373 May cause damage to organs through prolonged or repeated exposure.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.  
 P235 Keep cool.  
 P240 Ground / bond container and receiving equipment.  
 P241 Use explosion-proof electrical / ventilating / light / equipment.  
 P242 Use only non-sparking tools.  
 P243 Take precautionary measures against static discharge.  
 P260 Do not breathe mist / vapors / spray.  
 P264 Wash area of contact thoroughly after handling.  
 P272 Contaminated work clothing should not be allowed out of the workplace.  
 P280 Wear protective gloves / eye protection / face protection.  
 P302+352 IF ON SKIN: Wash with soap and water.  
 P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.  
 P310 Immediately call a POISON CENTER or doctor / physician.  
 P314 Get Medical advice / attention if you feel unwell.  
 P333+313 If skin irritation or a rash occurs: Get medical advice/attention.  
 P362 Take off contaminated clothing and wash before reuse.  
 P363 Wash contaminated clothing before reuse.  
 P370 In case of fire: Use water spray, fog, or regular foam..  
 P403+233 Store in a well ventilated place. Keep container tightly closed.  
 P501 Dispose of contents / container in accordance with local / national regulations.

HMIS Rating                  Health: 2\*                  Flammability: 3                  Reactivity: 0

3. Composition/information on ingredients
---

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
EPOXY RESIN CAS Number: 0025036-25-3	10 - 25	Eye Irrit. 2;H319 Skin Irrit. 2;H315 Skin Sens. 1;H317	[1]
Magnesium silicate talc CAS Number: 0014807-96-6	10 - 25	Not Classified	[1][2]
Barium sulfate CAS Number: 0007727-43-7	10 - 25	Not Classified	[1][2]
Titanium dioxide (Non-respirable) CAS Number: 0013463-67-7	10 - 25	Not Classified	[1][2]
MICA CAS Number: 0012001-26-2	10 - 25	Not Classified	[1][2]
Butyl alcohol, n- CAS Number: 0000071-36-3	1.0 - 10	Flam. Liq. 3;H226 Acute Tox. 4;H302 STOT SE 3;H335 Skin Irrit. 2;H315 Eye Dam. 1;H318 STOT SE 3;H336	[1][2]
Xylene CAS Number: 0001330-20-7	1.0 - 10	Flam. Liq. 3;H226 Acute Tox. 4;H332 Acute Tox. 4;H312 Skin Irrit. 2;H315	[1][2]
Solvent naphtha (petroleum), light aromatic CAS Number: 0064742-95-6	1.0 - 10	Asp. Tox. 1;H304	[1]
1,2,4-trimethyl benzene CAS Number: 0000095-63-6	1.0 - 10	Flam. Liq. 3;H226 Acute Tox. 4;H332 Eye Irrit. 2;H319 STOT SE 3;H335	[1]

## Y2002E\_A9

		Skin Irrit. 2;H315 Aquatic Chronic 2;H411	
Ethyl Benzene CAS Number: 0000100-41-4	1.0 - 10	Flam. Liq. 2;H225 Acute Tox. 4;H332 STOT RE 2;H373 Asp. Tox. 1;H304	[1][2]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the phrases are shown in Section 16.

### 4. First aid measures

#### 4.1. Description of first aid measures

General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.
Ingestion	If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.

#### 4.2. Most important symptoms and effects, both acute and delayed

Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.
Inhalation	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.
Eyes	Causes severe eye irritation. Avoid contact with eyes.
Skin	Causes skin irritation. May be harmful if absorbed through the skin.
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.

### 5. Fire-fighting measures

#### 5.1. Extinguishing media

CAUTION: This product has a very low flashpoint. Use of water spray when fighting fire may be inefficient.  
CAUTION: For mixtures containing alcohol or polar solvent, alcohol-resistant foam may be more effective.  
SMALL FIRES: Use dry chemical, CO<sub>2</sub>, water spray or regular foam. LARGE FIRES: Use water spray, fog, or regular foam. Do not use straight streams. Move containers from fire area if you can do so without risk.

#### 5.2. Special hazards arising from the substance or mixture

No data available

#### 5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

ERG Guide No. 128

### 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.

#### 6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

### 6.3. Methods and material for containment and cleaning up

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).

## 7. Handling and storage

### 7.1. Precautions for safe handling

#### Handling

Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.

#### In Storage

Keep away from heat, sparks and flame.

### 7.2. Conditions for safe storage, including any incompatibilities

Store between 40-100F (4-38C).

Do not get in eyes, on skin or clothing.

Strong oxidizing agents.

Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.

### 7.3. Specific end use(s)

Close container after each use.

Wash thoroughly after handling.

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

## 8. Exposure controls and personal protection

### 8.1. Control parameters

#### Exposure

CAS No.	Ingredient	Source	Value
0000071-36-3	Butyl alcohol, n-	OSHA	100 ppm TWA; 300 mg/m <sup>3</sup> TWA50 ppm Ceiling; 150 mg/m <sup>3</sup> Ceiling
		ACGIH	20 ppm TWA
		NIOSH	50 ppm Ceiling; 150 mg/m <sup>3</sup> Ceiling1400 ppm IDLH (10% LEL)
		Supplier	No Established Limit
		OHSA, CAN	20 ppm TWA
		Mexico	20 ppm TWA VLE-PPT
		Brazil	40 ppm TWA LT; 115 mg/m <sup>3</sup> TWA LT
0000095-63-6	1,2,4-trimethyl benzene	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	25 ppm TWA; 125 mg/m <sup>3</sup> TWA
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0000100-41-4	Ethyl Benzene	OSHA	100 ppm TWA; 435 mg/m <sup>3</sup> TWA125 ppm STEL; 545 mg/m <sup>3</sup> STEL
		ACGIH	20 ppm TWA
		NIOSH	100 ppm TWA; 435 mg/m <sup>3</sup> TWA125 ppm STEL; 545 mg/m <sup>3</sup> STEL800 ppm IDLH (10% LEL)

## Y2002E\_A9

		Supplier	No Established Limit
		OHSA, CAN	20 ppm TWA
		Mexico	20 ppm TWA VLE-PPT
		Brazil	78 ppm TWA LT; 340 mg/m3 TWA LT
0001330-20-7	Xylene	OSHA	100 ppm TWA; 435 mg/m3 TWA150 ppm STEL; 655 mg/m3 STEL
		ACGIH	100 ppm TWA150 ppm STEL
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	100 ppm TWA150 ppm STEL
		Mexico	100 ppm TWA VLE-PPT150 ppm STEL [PPT-CT]
		Brazil	78 ppm TWA LT; 340 mg/m3 TWA LT
0007727-43-7	Barium sulfate	OSHA	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
		ACGIH	5 mg/m3 TWA (inhalable particulate matter, particulate matter containing no asbestos and
		NIOSH	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
		Supplier	No Established Limit
		OHSA, CAN	5 mg/m3 TWA (particulate matter containing no Asbestos and
		Mexico	10 mg/m3 TWA VLE-PPT
		Brazil	No Established Limit
0012001-26-2	MICA	OSHA	No Established Limit
		ACGIH	3 mg/m3 TWA (respirable particulate matter)
		NIOSH	3 mg/m3 TWA (containing
		Supplier	No Established Limit
		OHSA, CAN	3 mg/m3 TWA (respirable)
		Mexico	3 mg/m3 TWA VLE-PPT (respirable fraction)
		Brazil	No Established Limit
0013463-67-7	Titanium dioxide (Non-respirable)	OSHA	15 mg/m3 TWA (total dust)
		ACGIH	10 mg/m3 TWA
		NIOSH	2.4 mg/m3 TWA (CIB 63, fine); 0.3 mg/m3 TWA (CIB 63, ultrafine, including engineered nanoscale)5000 mg/m3 IDLH
		Supplier	No Established Limit
		OHSA, CAN	10 mg/m3 TWA
		Mexico	10 mg/m3 TWA VLE-PPT
		Brazil	No Established Limit
0014807-96-6	Magnesium silicate talc	OSHA	No Established Limit
		ACGIH	2 mg/m3 TWA (particulate matter containing no asbestos and
		NIOSH	2 mg/m3 TWA (containing no Asbestos and
		Supplier	No Established Limit
		OHSA, CAN	2 mg/m3 TWA (containing no Asbestos and
		Mexico	2 mg/m3 TWA VLE-PPT (particulate matter containing no asbestos and
		Brazil	No Established Limit
0025036-25-3	EPOXY RESIN	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit

Y2002E\_A9

0064742-95-6	Solvent naphtha (petroleum), light aromatic	Mexico	No Established Limit
		Brazil	No Established Limit
		OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
Brazil	No Established Limit		

Health Data

CAS No.	Ingredient	Source	Value
0000071-36-3	Butyl alcohol, n-	NIOSH	Eye and mucous membrane irritation CNS depression
0000095-63-6	1,2,4-trimethyl benzene	NIOSH	No Established Limit
0000100-41-4	Ethyl Benzene	NIOSH	Eye skin
0001330-20-7	Xylene	NIOSH	Central nervous system depressant; respiratory and eye irritation
0007727-43-7	Barium sulfate	NIOSH	Eye nose
0012001-26-2	MICA	NIOSH	respirable dust; Fibrotic pneumoconiosis
0013463-67-7	Titanium dioxide (Non-respirable)	NIOSH	Lung tumors in animals
0014807-96-6	Magnesium silicate talc	NIOSH	(containing asbestos); Fibrotic pneumoconiosis; (containing no asbestos); Nonmalignant respiratory effects
0025036-25-3	EPOXY RESIN	NIOSH	No Established Limit
0064742-95-6	Solvent naphtha (petroleum), light aromatic	NIOSH	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000071-36-3	Butyl alcohol, n-	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000095-63-6	1,2,4-trimethyl benzene	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000100-41-4	Ethyl Benzene	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0001330-20-7	Xylene	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0007727-43-7	Barium sulfate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0012001-26-2	MICA	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0013463-67-7	Titanium dioxide (Non-respirable)	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;

Y2002E\_A9

0014807-96-6	Magnesium silicate talc	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0025036-25-3	EPOXY RESIN	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064742-95-6	Solvent naphtha (petroleum), light aromatic	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

Respiratory	Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.
Eyes	Avoid contact with eyes. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products. When there is a risk of ignition from static electricity, wear antistatic protective clothing and footwear. Any additional personal protective equipment or measures should be selected based on the risk assessment of the task being performed and should be approved by a specialist before handling this product.
Engineering Controls	Depending on the site-specific conditions of use, provide adequate ventilation.
Other Work Practices	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

9. Physical and chemical properties

Appearance	Coloured Liquid
Odor threshold	Not Measured
pH	No Established Limit
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	76 (°C) 169 (°F) (boiling range not measured)
Flash Point	27 (°C) 80 (°F)
Evaporation rate (Ether = 1)	Not Measured
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: .1 Upper Explosive Limit: No Established Limit
vapor pressure (Pa)	Not Measured
Vapor Density	Heavier than air
Specific Gravity	1.56
Solubility in Water	Not Measured
Partition coefficient n-octanol/water (Log Kow)	Not Measured

## Y2002E\_A9

Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	No Established Limit Not Measured
VOC %	Refer to the Technical Data Sheet or label where information is available.
VOHAP content (gm/litre of paint)	265.08 (as supplied)
VOHAP content (gm/litre of Solid Coating)	142.39 (as supplied)

### 10. Stability and reactivity

#### 10.1. Reactivity

No data available

#### 10.2. Chemical stability

This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.

#### 10.3. Possibility of hazardous reactions

No data available

#### 10.4. Conditions to avoid

No data available

#### 10.5. Incompatible materials

Strong oxidizing agents.

#### 10.6. Hazardous decomposition products

No data available

### 11. Toxicological information

#### Acute toxicity

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr
EPOXY RESIN - (25036-25-3)	No data available	No data available	No data available	No data available
Magnesium silicate talc - (14807-96-6)	No data available	No data available	No data available	No data available
Barium sulfate - (7727-43-7)	3,000.00, Mouse - Category: 5	No data available	No data available	No data available
Titanium dioxide (Non-respirable) - (13463-67-7)	5,001.00, Mouse - Category: NA	10,000.00, Rabbit - Category: NA	No data available	6.82, Rat - Category: NA
MICA - (12001-26-2)	No data available	No data available	No data available	No data available
Butyl alcohol, n- - (71-36-3)	2,292.00, Rat - Category: 5	3,430.00, Rabbit - Category: 5	No data available	No data available
Xylene - (1330-20-7)	4,299.00, Rat - Category: 5	1,548.00, Rabbit - Category: 4	No data available	20.00, Rat - Category: NA
Solvent naphtha (petroleum), light aromatic - (64742-95-6)	6,800.00, Rat - Category: NA	3,400.00, Rabbit - Category: 5	No data available	No data available
1,2,4-trimethyl benzene - (95-63-6)	3,400.00, Rat - Category: 5	3,160.00, Rabbit - Category: 5	18.00, Rat - Category: 4	No data available
Ethyl Benzene - (100-41-4)	3,500.00, Rat - Category: 5	15,433.00, Rabbit -	17.20, Rat - Category: 4	No data available



## Y2002E\_A9

Category: NA

Item	Category	Hazard
Acute Toxicity (mouth)	Not Classified	Not Applicable
Acute Toxicity (skin)	Not Classified	Not Applicable
Acute Toxicity (inhalation)	Not Classified	Not Applicable
Skin corrosion/irritation	2	Causes skin irritation.
Eye damage/irritation	1	Causes serious eye damage.
Sensitization (respiratory)	Not Classified	Not Applicable
Sensitization (skin)	1	May cause an allergic skin reaction.
Germ toxicity	Not Classified	Not Applicable
Carcinogenicity	Not Classified	Not Applicable
Reproductive Toxicity	Not Classified	Not Applicable
Specific target organ systemic Toxicity (repeated exposure)	2	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	Not Classified	Not Applicable

## 12. Ecological information

## 12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

## Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
EPOXY RESIN - (25036-25-3)	Not Available	Not Available	Not Available
Magnesium silicate talc - (14807-96-6)	Not Available	Not Available	Not Available
Barium sulfate - (7727-43-7)	59,000.00, Poecilia sphenops	32.00, Daphnia magna	Not Available
Titanium dioxide (Non-respirable) - (13463-67-7)	294.00, Oryzias latipes	501.00, Daphnia magna	51.00 (72 hr), Pseudokirchnerella subcapitata
MICA - (12001-26-2)	Not Available	Not Available	Not Available
Butyl alcohol, n- - (71-36-3)	1,376.00, Pimephales promelas	1,328.00, Daphnia magna	500.00 (96 hr), Scenedesmus subspicatus
Xylene - (1330-20-7)	3.30, Oncorhynchus mykiss	8.50, Palaemonetes pugio	100.00 (72 hr), Chlorococcales
Solvent naphtha (petroleum), light aromatic - (64742-95-6)	9.22, Oncorhynchus mykiss	6.14, Daphnia magna	19.00 (72 hr), Selenastrum capricornutum
1,2,4-trimethyl benzene - (95-63-6)	7.72, Pimephales promelas	3.60, Daphnia magna	2.356 (96 hr), Green algae
Ethyl Benzene - (100-41-4)	4.20, Oncorhynchus mykiss	2.93, Daphnia magna	3.60 (96 hr), Pseudokirchneriella subcapitata

## 12.2. Persistence and degradability

No data available

## 12.3. Bioaccumulative potential

Not Measured

## 12.4. Mobility in soil

No data available

## 12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

## 12.6. Other adverse effects

No data available

13. Disposal considerations
-----------------------------

13.1. Waste treatment methods

Do not allow spills to enter drains or watercourses.

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information
---------------------------

14.1. UN number UN 1263

14.2. UN proper shipping name PAINT

14.3. Transport hazard class(es)

DOT (Domestic Surface Transportation)		IMO / IMDG (Ocean Transportation)	
Proper Shipping Name	PAINT	IMDG Proper Shipping Name	PAINT
Hazard Class	3 - Flammable	IMDG Hazard Class	3 - Flammable
		Sub Class	Not applicable
UN / NA Number	UN 1263		
Packing Group	III	IMDG Packing Group	III
CERCLA/DOT RQ	NA gal. / NA lbs.	System Reference Code	2

14.4. Packing group III

14.5. Environmental hazards

IMDG Marine Pollutant: No

14.6. Special precautions for user

Not Applicable

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

15. Regulatory information
----------------------------

Regulatory Overview    The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

WHMIS Classification    B2 D2B E

DOT Marine Pollutants (10%):  
(No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):  
(No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%) :

- Butyl alcohol, n- (5000 lb final RQ; 2270 kg final RQ)
- Ethyl Benzene (1000 lb final RQ; 454 kg final RQ)
- Xylene (100 lb final RQ; 45.4 kg final RQ)

EPCRA 302 Extremely Hazardous (>.1%) :  
(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%) :

- 1,2,4-trimethyl benzene
- Butyl alcohol, n-
- Ethyl Benzene
- Xylene

Mass RTK Substances (>1%) :

1,2,4-trimethyl benzene  
Barium sulfate  
Butyl alcohol, n-  
Ethyl Benzene  
Magnesium silicate talc  
MICA  
Titanium dioxide (Non-respirable)  
Xylene

Penn RTK Substances (>1%) :

1,2,4-trimethyl benzene  
Barium sulfate  
Butyl alcohol, n-  
Ethyl Benzene  
Magnesium silicate talc  
MICA  
Titanium dioxide (Non-respirable)  
Xylene

Penn Special Hazardous Substances (>.01%) :  
(No Product Ingredients Listed)

RCRA Status:  
(No Product Ingredients Listed)

N.J. RTK Substances (>1%) :

1,2,4-trimethyl benzene  
Barium sulfate  
Butyl alcohol, n-  
Ethyl Benzene  
Magnesium silicate talc  
MICA  
Titanium dioxide (Non-respirable)  
Xylene

N.J. Special Hazardous Substances (>.01%) :

2-Methylpropan-1-ol  
Cumene  
Butyl alcohol, n-  
Crystalline Silica - Quartz - Non-Respirable  
Ethanol  
Ethyl Benzene  
Isopropyl Alcohol  
Magnesium silicate talc  
Methanol  
Toluene  
Xylene

N.J. Env. Hazardous Substances (>.1%) :

1,2,4-trimethyl benzene  
Butyl alcohol, n-  
Ethyl Benzene  
Xylene

Proposition 65 - Carcinogens (>0%):

Formaldehyde  
Ethanol  
Benzene  
Cumene  
Ethyl Benzene  
Methyl Isobutyl Ketone  
Titanium dioxide (Non-respirable)

Proposition 65 - Female Repro Toxins (>0%):  
(No Product Ingredients Listed)

Proposition 65 - Male Repro Toxins (>0%):

Benzene

Proposition 65 - Developmental Toxins (>0%):

Ethanol

Methanol

Benzene

Methyl Isobutyl Ketone

Toluene

16. Other information
-----------------------

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H226 Flammable liquid and vapor.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

End of Document