

# Y5580\_B9

## Safety Data Sheet MICRON CSC BLUE



Bulk Sales Reference No.: Y5580  
SDS Revision Date: 10/21/2020  
SDS Revision Number: B9-8

### 1. Identification of the preparation and company

#### 1.1. Product identifier

Product Identity MICRON CSC BLUE  
Bulk Sales Reference No. Y5580

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended Use See Technical Data Sheet.

#### 1.3. Details of the supplier of the safety data sheet

Company Name Akzo Nobel Coatings  
Manufacturer:  
Akzo Nobel Coatings  
International Paint  
6001 Antoine Drive  
Houston, Texas 77091

#### Emergency

CHEMTREC (800) 424-9300  
International Paint (713) 527-3887  
Poison Control Center (800) 854-6813  
Customer Service  
International Paint (800) 589-1267  
Fax No. (800) 631-7481

### 2. Hazard identification of the product

#### 2.1. Classification of the substance or mixture

Flam. Liq. 3;H226 Flammable liquid and vapor.  
Acute Tox. 4;H302 Harmful if swallowed.  
Acute Tox. 5;H313 May be harmful in contact with skin.  
Skin Irrit. 2;H315 Causes skin irritation.  
Eye Dam. 1;H318 Causes serious eye damage.  
Skin Sens. 1;H317 May cause an allergic skin reaction.  
STOT RE 2;H373 May cause damage to organs through prolonged or repeated exposure.  
Aquatic Chronic 1;H410 Very toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



Danger.

H226 Flammable liquid and vapor.  
H302 Harmful if swallowed.

H313 May be harmful in contact with skin.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H410 Very toxic to aquatic life with long lasting effects.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.  
 P235 Keep cool.  
 P240 Ground / bond container and receiving equipment.  
 P241 Use explosion-proof electrical / ventilating / light / equipment.  
 P242 Use only non-sparking tools.  
 P243 Take precautionary measures against static discharge.  
 P260 Do not breathe mist / vapors / spray.  
 P264 Wash area of contact thoroughly after handling.  
 P270 Do not eat, drink or smoke when using this product.  
 P272 Contaminated work clothing should not be allowed out of the workplace.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves / eye protection / face protection.  
 P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
 P302+352 IF ON SKIN: Wash with soap and water.  
 P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.  
 P312 Call a POISON CENTER or doctor / physician if you feel unwell.  
 P314 Get Medical advice / attention if you feel unwell.  
 P330 Rinse mouth.  
 P333+313 If skin irritation or a rash occurs: Get medical advice/attention.  
 P362 Take off contaminated clothing and wash before reuse.  
 P363 Wash contaminated clothing before reuse.  
 P370 In case of fire: Use water spray, fog, or regular foam..  
 P391 Collect spillage.  
 P403+233 Store in a well ventilated place. Keep container tightly closed.  
 P501 Dispose of contents / container in accordance with local / national regulations.

HMIS Rating            Health: 2\*            Flammability: 3            Reactivity: 0

3. Composition/information on ingredients
---

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Copper (I) oxide CAS Number: 0001317-39-1	25 - 50	Acute Tox. 4;H302 Aquatic Acute 1;H400 Aquatic Chronic 1;H410 Acute Tox. 4;H332 Eye Dam. 1;H318	[1]
Xylene CAS Number: 0001330-20-7	10 - 25	Flam. Liq. 3;H226 Acute Tox. 4;H332 Acute Tox. 4;H312 Skin Irrit. 2;H315	[1][2]
Rosin CAS Number: 0008050-09-7	10 - 25	Skin Sens. 1;H317	[1]
Zinc oxide CAS Number: 0001314-13-2	1.0 - 10	Aquatic Acute 1;H400 Aquatic Chronic 1;H410	[1][2]

Titanium dioxide (Non-respirable) CAS Number: 0013463-67-7	1.0 - 10	Not Classified	[1][2]
Borosilicate glass CAS Number: 0065997-17-3	1.0 - 10	Eye Irrit. 2;H319	[1]
Solvent naphtha (petroleum), light aromatic CAS Number: 0064742-95-6	1.0 - 10	Asp. Tox. 1;H304	[1]
Ethyl Benzene CAS Number: 0000100-41-4	1.0 - 10	Flam. Liq. 2;H225 Acute Tox. 4;H332 STOT RE 2;H373 Asp. Tox. 1;H304	[1][2]
1,2,4-trimethyl benzene CAS Number: 0000095-63-6	1.0 - 10	Flam. Liq. 3;H226 Acute Tox. 4;H332 Eye Irrit. 2;H319 STOT SE 3;H335 Skin Irrit. 2;H315 Aquatic Chronic 2;H411	[1]
ETHYLTOLUENESULFONAMIDE CAS Number: 0008047-99-2	1.0 - 10	----	[1]
Blue pigment CAS Number: 0000147-14-8	1.0 - 10	Not Classified	[1]
Organoclay CAS Number: 0068911-87-5	1.0 - 10	Not Classified	[1]
001317-38-0 CAS Number: 0001317-38-0	1.0 - 10	Aquatic Acute 1;H400 Aquatic Chronic 1;H410	[1]
1,3,5-trimethylbenzene CAS Number: 0000108-67-8	1.0 - 10	Flam. Liq. 3;H226 STOT SE 3;H335 Aquatic Chronic 2;H411	[1]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the phrases are shown in Section 16.

#### 4. First aid measures

##### 4.1. Description of first aid measures

General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.
Ingestion	If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.

##### 4.2. Most important symptoms and effects, both acute and delayed

Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.
Inhalation	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.
Eyes	Causes severe eye irritation. Avoid contact with eyes.
Skin	Causes skin irritation. May be harmful if absorbed through the skin.
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.

5. Fire-fighting measures
---------------------------

## 5.1. Extinguishing media

CAUTION: This product has a very low flashpoint. Use of water spray when fighting fire may be inefficient. CAUTION: For mixtures containing alcohol or polar solvent, alcohol-resistant foam may be more effective. SMALL FIRES: Use dry chemical, CO<sub>2</sub>, water spray or regular foam. LARGE FIRES: Use water spray, fog, or regular foam. Do not use straight streams. Move containers from fire area if you can do so without risk.

## 5.2. Special hazards arising from the substance or mixture

No data available

## 5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

ERG Guide No. 128

6. Accidental release measures
--------------------------------

## 6.1. Personal precautions, protective equipment and emergency procedures

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.

## 6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

## 6.3. Methods and material for containment and cleaning up

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).

7. Handling and storage
-------------------------

## 7.1. Precautions for safe handling

## Handling

Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.

## In Storage

Keep away from heat, sparks and flame.

## 7.2. Conditions for safe storage, including any incompatibilities

Store between 40-100F (4-38C).

Do not get in eyes, on skin or clothing.

Strong oxidizing agents.

Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.

## 7.3. Specific end use(s)

Close container after each use.

Wash thoroughly after handling.

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

8. Exposure controls and personal protection
--

## 8.1. Control parameters

## Exposure

CAS No.	Ingredient	Source	Value
0000095-63-6	1,2,4-trimethyl benzene	OSHA	No Established Limit

## Y5580\_B9

		ACGIH	No Established Limit
		NIOSH	25 ppm TWA; 125 mg/m <sup>3</sup> TWA
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0000100-41-4	Ethyl Benzene	OSHA	100 ppm TWA; 435 mg/m <sup>3</sup> TWA125 ppm STEL; 545 mg/m <sup>3</sup> STEL
		ACGIH	20 ppm TWA
		NIOSH	100 ppm TWA; 435 mg/m <sup>3</sup> TWA125 ppm STEL; 545 mg/m <sup>3</sup> STEL800 ppm IDLH (10% LEL)
		Supplier	No Established Limit
		OHSA, CAN	20 ppm TWA
		Mexico	20 ppm TWA VLE-PPT
		Brazil	78 ppm TWA LT; 340 mg/m <sup>3</sup> TWA LT
0000108-67-8	1,3,5-trimethylbenzene	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	25 ppm TWA; 125 mg/m <sup>3</sup> TWA
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0000147-14-8	Blue pigment	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0001314-13-2	Zinc oxide	OSHA	5 mg/m <sup>3</sup> TWA (fume); 15 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction)10 mg/m <sup>3</sup> STEL (fume)
		ACGIH	2 mg/m <sup>3</sup> TWA (respirable particulate matter)10 mg/m <sup>3</sup> STEL (respirable particulate matter)
		NIOSH	5 mg/m <sup>3</sup> TWA (dust and fume)10 mg/m <sup>3</sup> STEL (fume)15 mg/m <sup>3</sup> Ceiling (dust)500 mg/m <sup>3</sup> IDLH
		Supplier	No Established Limit
		OHSA, CAN	2 mg/m <sup>3</sup> TWA (respirable)10 mg/m <sup>3</sup> STEL (respirable)
		Mexico	2 mg/m <sup>3</sup> TWA VLE-PPT (respirable fraction)10 mg/m <sup>3</sup> STEL [PPT-CT] (respirable fraction)
		Brazil	No Established Limit
0001317-38-0	001317-38-0	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	0.1 mg/m <sup>3</sup> TWA (fume, as Cu)
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0001317-39-1	Copper (I) oxide	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
			No Established Limit

Y5580\_B9

		OHSA, CAN	
		Mexico	No Established Limit
		Brazil	No Established Limit
0001330-20-7	Xylene	OSHA	100 ppm TWA; 435 mg/m3 TWA150 ppm STEL; 655 mg/m3 STEL
		ACGIH	100 ppm TWA150 ppm STEL
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	100 ppm TWA150 ppm STEL
		Mexico	100 ppm TWA VLE-PPT150 ppm STEL [PPT-CT]
		Brazil	78 ppm TWA LT; 340 mg/m3 TWA LT
0008047-99-2	ETHYLTOLUENESULFONAMIDE	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0008050-09-7	Rosin	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	exposure by all routes should be carefully controlled to levels as low as possible, listed unde
		Mexico	No Established Limit
		Brazil	No Established Limit
0013463-67-7	Titanium dioxide (Non-respirable)	OSHA	15 mg/m3 TWA (total dust)
		ACGIH	10 mg/m3 TWA
		NIOSH	2.4 mg/m3 TWA (CIB 63, fine); 0.3 mg/m3 TWA (CIB 63, ultrafine, including engineered nanoscale)5000 mg/m3 IDLH
		Supplier	No Established Limit
		OHSA, CAN	10 mg/m3 TWA
		Mexico	10 mg/m3 TWA VLE-PPT
		Brazil	No Established Limit
0064742-95-6	Solvent naphtha (petroleum), light aromatic	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0065997-17-3	Borosilicate glass	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0068911-87-5	Organoclay	OSHA	No Established Limit
		ACGIH	No Established Limit

## Y5580\_B9

	NIOSH	No Established Limit
	Supplier	No Established Limit
	OHSA, CAN	No Established Limit
	Mexico	No Established Limit
	Brazil	No Established Limit

## Health Data

CAS No.	Ingredient	Source	Value
0000095-63-6	1,2,4-trimethyl benzene	NIOSH	No Established Limit
0000100-41-4	Ethyl Benzene	NIOSH	Eye skin
0000108-67-8	1,3,5-trimethylbenzene	NIOSH	No Established Limit
0000147-14-8	Blue pigment	NIOSH	No Established Limit
0001314-13-2	Zinc oxide	NIOSH	Metal fume fever
0001317-38-0	001317-38-0	NIOSH	No Established Limit
0001317-39-1	Copper (I) oxide	NIOSH	No Established Limit
0001330-20-7	Xylene	NIOSH	Central nervous system depressant; respiratory and eye irritation
0008047-99-2	ETHYLTOLUENESULFONAMIDE	NIOSH	No Established Limit
0008050-09-7	Rosin	NIOSH	No Established Limit
0013463-67-7	Titanium dioxide (Non-respirable)	NIOSH	Lung tumors in animals
0064742-95-6	Solvent naphtha (petroleum), light aromatic	NIOSH	No Established Limit
0065997-17-3	Borosilicate glass	NIOSH	No Established Limit
0068911-87-5	Organoclay	NIOSH	No Established Limit

## Carcinogen Data

CAS No.	Ingredient	Source	Value
0000095-63-6	1,2,4-trimethyl benzene	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000100-41-4	Ethyl Benzene	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0000108-67-8	1,3,5-trimethylbenzene	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000147-14-8	Blue pigment	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0001314-13-2	Zinc oxide	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0001317-38-0	001317-38-0	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0001317-39-1	Copper (I) oxide	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0001330-20-7	Xylene	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;

Y5580\_B9

0008047-99-2	ETHYLTOLUENESULFONAMIDE	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0008050-09-7	Rosin	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0013463-67-7	Titanium dioxide (Non-respirable)	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0064742-95-6	Solvent naphtha (petroleum), light aromatic	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0065997-17-3	Borosilicate glass	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0068911-87-5	Organoclay	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

Respiratory	Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.
Eyes	Avoid contact with eyes. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products. When there is a risk of ignition from static electricity, wear antistatic protective clothing and footwear. Any additional personal protective equipment or measures should be selected based on the risk assessment of the task being performed and should be approved by a specialist before handling this product.
Engineering Controls	Depending on the site-specific conditions of use, provide adequate ventilation.
Other Work Practices	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

9. Physical and chemical properties
-------------------------------------

Appearance	Coloured Liquid
Odor threshold	Not Measured
pH	No Established Limit
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	46 (°C) 115 (°F)
Flash Point	27 (°C) 80 (°F)



## Y5580\_B9

Evaporation rate (Ether = 1)	Not Measured
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: .6 Upper Explosive Limit: No Established Limit
vapor pressure (Pa)	Not Measured
Vapor Density	Heavier than air
Specific Gravity	1.80
Solubility in Water	Not Measured
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	No Established Limit Not Measured
VOC %	Refer to the Technical Data Sheet or label where information is available.
VOHAP content (gm/litre of paint)	452.25 (as supplied)
VOHAP content (gm/litre of Solid Coating)	255.72 (as supplied)

### 10. Stability and reactivity

#### 10.1. Reactivity

No data available

#### 10.2. Chemical stability

This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.

#### 10.3. Possibility of hazardous reactions

No data available

#### 10.4. Conditions to avoid

No data available

#### 10.5. Incompatible materials

Strong oxidizing agents.

#### 10.6. Hazardous decomposition products

No data available

### 11. Toxicological information

#### Acute toxicity

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr
Copper (I) oxide - (1317-39-1)	470.00, Rat - Category: 4	2,000.00, Rabbit - Category: 4	No data available	50.00, Rat - Category: NA
Xylene - (1330-20-7)	4,299.00, Rat - Category: 5	1,548.00, Rabbit - Category: 4	No data available	20.00, Rat - Category: NA
Rosin - (8050-09-7)	2,001.00, Rat - Category: 5	2,001.00, Rat - Category: 5	No data available	No data available
Zinc oxide - (1314-13-2)	5,000.00, Rat - Category: 5	No data available	No data available	2.50, Mouse - Category: 4
Titanium dioxide (Non-respirable) - (13463-67-7)	5,001.00, Mouse - Category: NA	10,000.00, Rabbit - Category: NA	No data available	6.82, Rat - Category: NA
Borosilicate glass - (65997-17-3)				

## Y5580\_B9

	No data available	No data available	No data available	No data available
Solvent naphtha (petroleum), light aromatic - (64742-95-6)	6,800.00, Rat - Category: NA	3,400.00, Rabbit - Category: 5	No data available	No data available
Ethyl Benzene - (100-41-4)	3,500.00, Rat - Category: 5	15,433.00, Rabbit - Category: NA	17.20, Rat - Category: 4	No data available
1,2,4-trimethyl benzene - (95-63-6)	3,400.00, Rat - Category: 5	3,160.00, Rabbit - Category: 5	18.00, Rat - Category: 4	No data available
ETHYLTOLUENESULFONAMIDE - (8047-99-2)	No data available	No data available	No data available	No data available
Blue pigment - (147-14-8)	6,401.00, Rat - Category: NA	5,001.00, Rat - Category: NA	No data available	No data available
Organoclay - (68911-87-5)	No data available	No data available	No data available	No data available
001317-38-0 - (1317-38-0)	2,500.00, Rat - Category: 5	2,001.00, Rat - Category: 5	No data available	No data available
1,3,5-trimethylbenzene - (108-67-8)	No data available	No data available	24.00, Rat - Category: NA	No data available

Item	Category	Hazard
Acute Toxicity (mouth)	4	Harmful if swallowed.
Acute Toxicity (skin)	5	May be harmful in contact with skin.
Acute Toxicity (inhalation)	Not Classified	Not Applicable
Skin corrosion/irritation	2	Causes skin irritation.
Eye damage/irritation	1	Causes serious eye damage.
Sensitization (respiratory)	Not Classified	Not Applicable
Sensitization (skin)	1	May cause an allergic skin reaction.
Germ toxicity	Not Classified	Not Applicable
Carcinogenicity	Not Classified	Not Applicable
Reproductive Toxicity	Not Classified	Not Applicable
Specific target organ systemic Toxicity (repeated exposure)	2	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	Not Classified	Not Applicable

## 12. Ecological information

## 12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

## Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Copper (I) oxide - (1317-39-1)	0.075, Danio rerio	0.042, Daphnia similis	0.03 (96 hr), Pseudokirchneriella subcapitata
Xylene - (1330-20-7)	3.30, Oncorhynchus mykiss	8.50, Palaemonetes pugio	100.00 (72 hr), Chlorococcales
Rosin - (8050-09-7)	1.70, Pimephales promelas	10.00, Daphnia magna	16.60 (72 hr), Pseudokirchneriella subcapitata
Zinc oxide - (1314-13-2)	1.10, Oncorhynchus mykiss	0.098, Daphnia magna	0.042 (72 hr), Pseudokirchneriella subcapitata
Titanium dioxide (Non-respirable) - (13463-67-7)	294.00, Oryzias latipes	501.00, Daphnia magna	51.00 (72 hr), Pseudokirchneriella subcapitata
Borosilicate glass - (65997-17-3)	Not Available	Not Available	Not Available

Y5580\_B9

Solvent naphtha (petroleum), light aromatic - (64742-95-6)	9.22, Oncorhynchus mykiss	6.14, Daphnia magna	19.00 (72 hr), Selenastrum capricornutum
Ethyl Benzene - (100-41-4)	4.20, Oncorhynchus mykiss	2.93, Daphnia magna	3.60 (96 hr), Pseudokirchneriella subcapitata
1,2,4-trimethyl benzene - (95-63-6)	7.72, Pimephales promelas	3.60, Daphnia magna	2.356 (96 hr), Green algae
ETHYLTOLUENESULFONAMIDE - (8047-99-2)	Not Available	Not Available	Not Available
Blue pigment - (147-14-8)	101.00, Danio rerio	501.00, Daphnia magna	101.00 (72 hr), Desmodesmus subspicatus
Organoclay - (68911-87-5)	Not Available	Not Available	Not Available
001317-38-0 - (1317-38-0)	25.40, Oncorhynchus mykiss	0.011, Daphnia magna	0.014 (72 hr), Pseudokirchneriella subcapitata
1,3,5-trimethylbenzene - (108-67-8)	12.52, Carassius auratus	6.00, Daphnia magna	25.00 (48 hr), Scenedesmus subspicatus

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available

13. Disposal considerations

13.1. Waste treatment methods

Do not allow spills to enter drains or watercourses.

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information

14.1. UN number UN 1263

14.2. UN proper shipping name PAINT

14.3. Transport hazard class(es)

DOT (Domestic Surface Transportation)

Proper Shipping Name PAINT

Hazard Class 3 - Flammable

UN / NA Number UN 1263

Packing Group III

CERCLA/DOT RQ 60 gal. / 908 lbs.

IMO / IMDG (Ocean Transportation)

IMDG Proper Shipping Name PAINT

IMDG Hazard Class 3 - Flammable  
Sub Class Not applicable

IMDG Packing Group III

System Reference Code 2

14.4. Packing group III

14.5. Environmental hazards

IMDG Marine Pollutant: Yes ( Copper (I) oxide )

14.6. Special precautions for user

Not Applicable

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code  
Not Applicable

15. Regulatory information
----------------------------

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

WHMIS Classification B2 D2B E

DOT Marine Pollutants (10%):

(No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):

(No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%) :

Cumene (5000 lb final RQ; 2270 kg final RQ)

Copper (5000 lb final RQ (no reporting of releases of this hazardous substance is required if the diame)

Ethyl Benzene (1000 lb final RQ; 454 kg final RQ)

Xylene (100 lb final RQ; 45.4 kg final RQ)

EPCRA 302 Extremely Hazardous (>.1%) :

(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%) :

1,2,4-trimethyl benzene

Cumene

Copper

Ethyl Benzene

Xylene

Mass RTK Substances (>1%) :

1,2,4-trimethyl benzene

1,3,5-trimethylbenzene

Ethyl Benzene

Titanium dioxide (Non-respirable)

Xylene

Zinc oxide

Penn RTK Substances (>1%) :

1,2,4-trimethyl benzene

Ethyl Benzene

Titanium dioxide (Non-respirable)

Xylene

Zinc oxide

Penn Special Hazardous Substances (>.01%) :

(No Product Ingredients Listed)

RCRA Status:

(No Product Ingredients Listed)

N.J. RTK Substances (>1%) :

1,2,4-trimethyl benzene

Ethyl Benzene

Titanium dioxide (Non-respirable)

Xylene

Zinc oxide

N.J. Special Hazardous Substances (>.01%) :

2-Butoxy-ethanol

Cumene

Cristobalite

Ethyl Benzene

Toluene

Xylene

## N.J. Env. Hazardous Substances (&gt;.1%) :

1,2,4-trimethyl benzene  
Cumene  
Copper  
Ethyl Benzene  
Xylene

## Proposition 65 - Carcinogens (&gt;0%):

Cumene  
Ethyl Benzene  
Lead  
Cadmium  
Titanium dioxide (Non-respirable)

## Proposition 65 - Female Repro Toxins (&gt;0%):

Lead

## Proposition 65 - Male Repro Toxins (&gt;0%):

Lead  
Cadmium

## Proposition 65 - Developmental Toxins (&gt;0%):

Toluene  
Lead  
Cadmium

16. Other information
-----------------------

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.  
H226 Flammable liquid and vapor.  
H302 Harmful if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.

End of Document