



- P235 Keep cool.
- P240 Ground / bond container and receiving equipment.
- P241 Use explosion-proof electrical / ventilating / light / equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P273 Avoid release to the environment.
- P280 Wear protective gloves / eye protection / face protection.
- P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.
- P332+313 If skin irritation occurs: Get medical advice/attention.
- P337 If eye irritation persists:.
- P370 In case of fire: Use water spray, fog, or regular foam..
- P391 Collect spillage.
- P403+233 Store in a well ventilated place. Keep container tightly closed.
- P501 Dispose of contents / container in accordance with local / national regulations.

HMIS Rating            Health: Unknown            Flammability: Unknown            Reactivity: Unknown

### 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Butoxyl CAS Number: 0004435-53-4	25 - 50	Eye Irrit. 2;H319	[1]
Propylene glycol monomethyl ether acetate CAS Number: 0000108-65-6	10 - 25	Flam. Liq. 3;H226	[1]
Xylenes (o-, m-, p- isomers) CAS Number: 0001330-20-7	1.0 - 10	Flam. Liq. 3;H226 Acute Tox. 4;H332 Acute Tox. 4;H312 Skin Irrit. 2;H315 Eye Irrit. 2;H319 STOT SE 3;H335 Asp. Tox. 1;H304	[1][2]
COPPER, [29H,31H-PHTHALOCYANINATO(2-)-N29,N30,N31, CAS Number: 0068987-63-3	1.0 - 10	----	[1]
Carbon black CAS Number: 0001333-86-4	1.0 - 10	----	[1][2]
Cellulose, acetate butanoate CAS Number: 0009004-36-8	1.0 - 10	----	[1]
Titanium dioxide CAS Number: 0013463-67-7	1.0 - 10	----	[1][2]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the phrases are shown in Section 16.

### 4. First aid measures

#### 4.1. Description of first aid measures

General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.

## YHK990\_E2

Ingestion	If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.
4.2. Most important symptoms and effects, both acute and delayed	
Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.
Inhalation	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.
Eyes	Risk of serious damage to eyes. Do not get in eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific condition of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Skin	Causes skin irritation. May cause delayed skin irritation. May be harmful if absorbed through the skin.
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.
Chronic effects	Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.

### 5. Fire-fighting measures

#### 5.1. Extinguishing media

CAUTION: This product has a very low flashpoint. Use of water spray when fighting fire may be inefficient. SMALL FIRES: Use dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam. LARGE FIRES: Use water spray, fog, or alcohol-resistant foam. Do not use straight streams. Move containers from fire area if you can do so without risk. Runoff from fire control may cause pollution. Dike fire control water for later disposal. Do not scatter the material.

#### 5.2. Special hazards arising from the substance or mixture

May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide.

#### 5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

ERG Guide No.

### 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.

#### 6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

#### 6.3. Methods and material for containment and cleaning up

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).

### 7. Handling and storage

#### 7.1. Precautions for safe handling

##### Handling

Vapors may cause flash fire or ignite explosively.

##### In Storage

YHK990\_E2

Keep away from heat, sparks and flame.

7.2. Conditions for safe storage, including any incompatibilities

Store between 40-100F (4-38C).

Do not get in eyes, on skin or clothing.

Strong oxidizing agents.

Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.

7.3. Specific end use(s)

Close container after each use.

Wash thoroughly after handling.

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0000108-65-6	Propylene glycol monomethyl ether acetate	OSHA	
		ACGIH	
		NIOSH	
		Supplier	
		OHSA, CAN	50 ppm TWA; 270 mg/m3 TWA
		Mexico Brazil	
0001330-20-7	Xylenes (o-, m-, p- isomers)	OSHA	100 ppm TWA; 435 mg/m3 TWA 150 ppm STEL; 655 mg/m3 STEL
		ACGIH	100 ppm TWA 150 ppm STEL
		NIOSH	
		Supplier	
		OHSA, CAN	100 ppm TWA 150 ppm STEL
		Mexico Brazil	100 ppm TWA LMPE-PPT; 435 mg/m3 TWA LMPE-PPT 150 ppm STEL [LMPE-CT]; 655 mg/m3 STEL [LMPE-CT] 78 ppm TWA LT; 340 mg/m3 TWA LT
0001333-86-4	Carbon black	OSHA	3.5 mg/m3 TWA
		ACGIH	3 mg/m3 TWA (inhalable fraction)
		NIOSH	3.5 mg/m3 TWA; 0.1 mg/m3 TWA (Carbon black in presence of Polycyclic aromatic hydrocarbons, as 1750 mg/m3 IDLH)
		Supplier	
		OHSA, CAN	3 mg/m3 TWA (inhalable)
		Mexico Brazil	3.5 mg/m3 TWA LMPE-PPT 7 mg/m3 STEL [LMPE-CT]
0004435-53-4	Butoxyl	OSHA	
		ACGIH	
		NIOSH	
		Supplier	

YHK990\_E2

		OSHA, CAN	
		Mexico	
		Brazil	
0009004-36-8	Cellulose, acetate butanoate	OSHA	
		ACGIH	
		NIOSH	
		Supplier	
		OSHA, CAN	
		Mexico	
		Brazil	
0013463-67-7	Titanium dioxide	OSHA	15 mg/m3 TWA (total dust)
		ACGIH	10 mg/m3 TWA
		NIOSH	5000 mg/m3 IDLH
		Supplier	
		OSHA, CAN	10 mg/m3 TWA
		Mexico	10 mg/m3 TWA LMPE-PPT (as Ti)20 mg/m3 STEL [LMPE-CT] (as Ti)
		Brazil	
0068987-63-3	COPPER, [29H,31H-PHTHALOCYANINATO(2-)-N29,N30,N31,	OSHA	
		ACGIH	
		NIOSH	
		Supplier	
		OSHA, CAN	
		Mexico	
		Brazil	

Health Data

CAS No.	Ingredient	Source	Value
0000108-65-6	Propylene glycol monomethyl ether acetate	NIOSH	
0001330-20-7	Xylenes (o-, m-, p- isomers)	NIOSH	Central nervous system depressant; respiratory and eye irritation
0001333-86-4	Carbon black	NIOSH	Lung cardiovascular
0004435-53-4	Butoxyl	NIOSH	
0009004-36-8	Cellulose, acetate butanoate	NIOSH	
0013463-67-7	Titanium dioxide	NIOSH	Lung tumors in animals
0068987-63-3	COPPER, [29H,31H-PHTHALOCYANINATO(2-)-N29,N30,N31,	NIOSH	

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000108-65-6	Propylene glycol monomethyl ether acetate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0001330-20-7	Xylenes (o-, m-, p- isomers)	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0001333-86-4	Carbon black	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No;

## YHK990\_E2

0004435-53-4	Butoxyl		Group 4: No;
		OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
0009004-36-8	Cellulose, acetate butanoate	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
0013463-67-7	Titanium dioxide	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
0068987-63-3	COPPER, [29H,31H-PHTHALOCYANINATO(2-)-N29,N30,N31,	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No

### 8.2. Exposure controls

Respiratory	Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.
Eyes	Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Skin	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Engineering Controls	Depending on the site-specific conditions of use, provide adequate ventilation.
Other Work Practices	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

### 9. Physical and chemical properties

Appearance	Coloured Liquid
Odour threshold	Not Measured
pH	No Established Limit
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	124 (°C) 255 (°F)
Flash Point	47 (°C) 117 (°F)
Evaporation rate (Ether = 1)	Not Measured
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: .8

## YHK990\_E2

	Upper Explosive Limit: No Established Limit
vapor pressure (Pa)	Not Measured
Vapor Density	Heavier than air
Specific Gravity	1.08
Solubility in Water	Not Measured
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	No Established Limit Not Measured
VOC %	Refer to the Technical Data Sheet or label where information is available.

### 10. Stability and reactivity

#### 10.1. Reactivity

No data available

#### 10.2. Chemical stability

This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.

#### 10.3. Possibility of hazardous reactions

No data available

#### 10.4. Conditions to avoid

No data available

#### 10.5. Incompatible materials

Strong oxidizing agents.

#### 10.6. Hazardous decomposition products

May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide.

### 11. Toxicological information

#### Acute toxicity

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr
Butoxyl - (4435-53-4)	4,210.00, Rat - Category: 5	No data available	No data available	No data available
Propylene glycol monomethyl ether acetate - (108-65-6)	8,532.00, Rat - Category: NA	5,000.00, Rabbit - Category: 5	No data available	No data available
Xylenes (o-, m-, p- isomers) - (1330-20-7)	4,299.00, Rat - Category: 5	1,548.00, Rabbit - Category: 4	20.00, Rat - Category: 4	No data available
COPPER, [29H,31H-PHTHALOCYANINATO(2-)-N29,N30,N31, - (68987-63-3)	No data available	No data available	No data available	No data available
Carbon black - (1333-86-4)	8,000.00, Rat - Category: NA	3,000.00, Rabbit - Category: 5	No data available	No data available
Cellulose, acetate butanoate - (9004-36-8)				

YHK990\_E2

	6,400.00, Rat - Category: NA	1,000.00, Guinea Pig - Category: 3	No data available	No data available
Titanium dioxide - (13463-67-7)	10,000.00, Rat - Category: NA	10,000.00, Rabbit - Category: NA	No data available	6.82, Rat - Category: NA

Item	Category	Hazard
Acute Toxicity (mouth)	Not Classified	Not Applicable
Acute Toxicity (skin)	Not Classified	Not Applicable
Acute Toxicity (inhalation)	Not Classified	Not Applicable
Skin corrosion/irritation	3	Causes mild skin irritation.
Eye damage/irritation	2	Causes serious eye irritation.
Sensitization (respiratory)	Not Classified	Not Applicable
Sensitization (skin)	Not Classified	Not Applicable
Germ toxicity	Not Classified	Not Applicable
Carcinogenicity	Not Classified	Not Applicable
Reproductive Toxicity	Not Classified	Not Applicable
Specific target organ systemic toxicity (single exposure)	Not Classified	Not Applicable
Specific target organ systemic Toxicity (repeated exposure)	Not Classified	Not Applicable
Aspiration hazard	Not Classified	Not Applicable

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Butoxyl - (4435-53-4)	7.10, Danio rerio	360.00, Daphnia magna	Not Available
Propylene glycol monomethyl ether acetate - (108-65-6)	100.00, Salmo gairdneri	500.00, Daphnia magna	Not Available
Xylenes (o-, m-, p- isomers) - (1330-20-7)	3.30, Oncorhynchus mykiss	8.50, Palaemonetes pugio	100.00 (72 hr), Chlorococcales
COPPER, [29H,31H-PHTHALOCYANINATO(2-)-N29,N30,N31, - (68987-63-3)	Not Available	Not Available	0.00 ( hr),
Carbon black - (1333-86-4)	1,000.00, Danio rerio	5,600.00, Daphnia magna	10,000.00 (72 hr), Scenedesmus subspicatus
Cellulose, acetate butanoate - (9004-36-8)	Not Available	Not Available	Not Available
Titanium dioxide - (13463-67-7)	1,000.00, Fundulus heteroclitus	5.50, Daphnia magna	5.83 (72 hr), Pseudokirchneriella subcapitata

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available





Carbon black  
Titanium dioxide  
Xylenes (o-, m-, p- isomers)  
Penn RTK Substances (>1%) :  
Carbon black  
Titanium dioxide  
Xylenes (o-, m-, p- isomers)  
Penn Special Hazardous Substances (>.01%) :  
(No Product Ingredients Listed)  
RCRA Status:  
(No Product Ingredients Listed)  
N.J. RTK Substances (>1%) :  
Butoxyl  
Carbon black  
Titanium dioxide  
Xylenes (o-, m-, p- isomers)  
N.J. Special Hazardous Substances (>.01%) :  
Carbon black  
BUTYL ACETATE  
Xylenes (o-, m-, p- isomers)  
N.J. Env. Hazardous Substances (>.1%) :  
Xylenes (o-, m-, p- isomers)  
Proposition 65 - Carcinogens (>0%):  
Carbon black  
Quartz  
Titanium dioxide  
Proposition 65 - Female Repro Toxins (>0%):  
(No Product Ingredients Listed)  
Proposition 65 - Male Repro Toxins (>0%):  
(No Product Ingredients Listed)  
Proposition 65 - Developmental Toxins (>0%):  
(No Product Ingredients Listed)

16. Other information
-----------------------

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H226 Flammable liquid and vapor.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H336 May cause drowsiness or dizziness.  
H372 Causes damage to organs through prolonged or repeated exposure.

This is the first revision of this SDS format, changes from previous revision not applicable.

End of Document