

## SAFETY DATA SHEET

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Product name** : Perfection Pro YSC030 Spray Binder

**MSDS code** : R62069

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

| Identified uses                               |        |
|---|--------|
| Professional application of coatings and inks |        |
| Uses advised against                          | Reason |
| For professional use only.                    |        |

#### 1.3 Details of the supplier of the safety data sheet

**Supplier** : International Paint Ltd.  
Stoneygate Lane  
Felling  
Gateshead  
Tyne & Wear  
NE10 0JY  
United Kingdom  
Tel: +44 (0)191 469 6111 Fax: +44 (0)191 438 3711  
www.akzonobel.com/yacht

**e-mail address of person responsible for this SDS** : sds-cr@akzonobel.com

#### 1.4 Emergency telephone number

##### National advisory body/Poison Centre

**Telephone number** : Not available.

##### Supplier

**Telephone number** : + 31 (0)71 308 6944

**Hours of operation** : 24 hours

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

STOT SE 3, H336

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

## SECTION 2: Hazards identification

### 2.2 Label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : Flammable liquid and vapour.  
 May cause drowsiness or dizziness.  
 Harmful to aquatic life with long lasting effects.

### Precautionary statements

Prevention : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
 No smoking.

Response : Not applicable.

Storage : Store in a well-ventilated place.

Disposal : Not applicable.

Hazardous ingredients : n-butyl acetate

Supplemental label elements : Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

### Special packaging requirements

Containers to be fitted with child-resistant fastenings : Not applicable.

Tactile warning of danger : Not applicable.

### 2.3 Other hazards

Other hazards which do not result in classification : None known.

## SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

| Product/ingredient name                  | Identifiers   | %         | Classification<br>Regulation (EC) No.<br>1272/2008 [CLP]       | Type    |
|--|---|-----------|--|---------|
| n-butyl acetate                          | EC: 204-658-1<br>CAS: 123-86-4<br>Index: 607-025-00-1   | ≥25 - <50 | Flam. Liq. 3, H226<br>STOT SE 3, H336<br>EUH066                | [1] [2] |
| heptan-2-one                             | EC: 203-767-1<br>CAS: 110-43-0                          | ≥5 - <10  | Flam. Liq. 3, H226<br>Acute Tox. 4, H302<br>Acute Tox. 4, H332 | [1] [2] |
| Solvent naphtha (petroleum), light arom. | EC: 265-199-0<br>CAS: 64742-95-6<br>Index: 649-356-00-4 | ≥2 - <3   | Asp. Tox. 1, H304<br>Aquatic Chronic 2, H411<br>EUH066         | [1]     |
| 2-methoxy-1-methylethyl acetate          | EC: 203-603-9<br>CAS: 108-65-6                          | ≥1 - <3   | Flam. Liq. 3, H226   | [2]     |

Date of issue/Date of revision : 10/24/2016. Version : 1

Date of previous issue : 10/14/2016. 2/14

### SECTION 3: Composition/information on ingredients

|                        |   |         |  |         |
|------------------------|---|---------|--|---------|
| 1,2,4-trimethylbenzene | Index: 607-195-00-7<br>EC: 202-436-9<br>CAS: 95-63-6<br>Index: 601-043-00-3 | ≥1 - <3 | Flam. Liq. 3, H226<br>Acute Tox. 4, H332<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>STOT SE 3, H335<br>Aquatic Chronic 2, H411<br><b>See Section 16 for the full text of the H statements declared above.</b> | [1] [2] |
|------------------------|---|---------|--|---------|

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

#### 4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from

## SECTION 4: First aid measures

short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

See toxicological information (Section 11)

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Recommended: alcohol-resistant foam, CO<sub>2</sub>, powders, water spray.
- Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

### 5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
- Special protective equipment for fire-fighters** : Appropriate breathing apparatus may be required.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

- : Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

### 6.3 Methods and material for containment and cleaning up

- : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

### 6.4 Reference to other sections

- : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

- 7.1 Precautions for safe handling** :
- Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits.
  - In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.
  - Mixture may charge electrostatically: always use earthing leads when transferring from one container to another.
  - Operators should wear antistatic footwear and clothing and floors should be of the conducting type.
  - Keep away from heat, sparks and flame. No sparking tools should be used.
  - Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.
  - Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.
  - Put on appropriate personal protective equipment (see Section 8).
  - Never use pressure to empty. Container is not a pressure vessel.
  - Always keep in containers made from the same material as the original one.
  - Comply with the health and safety at work laws.
  - Do not allow to enter drains or watercourses.
- Information on fire and explosion protection**
- Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

**Notes on joint storage**

Keep away from: oxidising agents, strong alkalis, strong acids.

**Additional information on storage conditions**

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

**Seveso II Directive - Reporting thresholds (in tonnes)**

**Danger criteria**

| Category  | Notification and MAPP threshold | Safety report threshold |
|---|---------------------------------|-------------------------|
| P5c: Flammable liquids 2 and 3 not falling under P5a or P5b | 5000                            | 50000                   |
| C6: Flammable (R10)   | 5000                            | 50000                   |

### 7.3 Specific end use(s)

**Recommendations** : Not available.

**Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

#### Occupational exposure limits

| Product/ingredient name         | Exposure limit values   |
|---------------------------------|---|
| n-butyl acetate                 | <b>EH40/2005 WELs (United Kingdom (UK), 12/2011).</b><br>STEL: 966 mg/m <sup>3</sup> 15 minutes.<br>STEL: 200 ppm 15 minutes.<br>TWA: 724 mg/m <sup>3</sup> 8 hours.<br>TWA: 150 ppm 8 hours.                       |
| heptan-2-one                    | <b>EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin.</b><br>STEL: 475 mg/m <sup>3</sup> 15 minutes.<br>STEL: 100 ppm 15 minutes.<br>TWA: 237 mg/m <sup>3</sup> 8 hours.<br>TWA: 50 ppm 8 hours. |
| 2-methoxy-1-methylethyl acetate | <b>EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin.</b><br>STEL: 548 mg/m <sup>3</sup> 15 minutes.<br>STEL: 100 ppm 15 minutes.<br>TWA: 274 mg/m <sup>3</sup> 8 hours.<br>TWA: 50 ppm 8 hours. |
| 1,2,4-trimethylbenzene          | <b>EH40/2005 WELs (United Kingdom (UK), 12/2011).</b><br>TWA: 125 mg/m <sup>3</sup> 8 hours.<br>TWA: 25 ppm 8 hours.  |

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### DNELs/DMELs

No DNELs/DMELs available.

#### PNECs

No PNECs available

### 8.2 Exposure controls

**Appropriate engineering controls** : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

#### Individual protection measures



## SECTION 8: Exposure controls/personal protection

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Use safety eyewear designed to protect against splash of liquids.

### Skin protection

#### Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

**Gloves** : For prolonged or repeated handling, use the following type of gloves:

May be used: nitrile rubber, neoprene, butyl rubber

The recommendation for the type or types of glove to use when handling this product is based on information from the following source:

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Body protection** : Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.

Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

**Recommended mask** :



P1A1

**Environmental exposure controls** : Do not allow to enter drains or watercourses.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

|  |   |
|--|---|
| Physical state                               | : Liquid.   |
| Colour                                       | : Product Specific Information  |
| Odour  | : Characteristic.   |
| Odour threshold                              | : Not available.  |
| pH   | : Acidic.   |
| Melting point/freezing point                 | : Not available.  |
| Initial boiling point and boiling range      | : 126°C   |
| Flash point                                  | : Closed cup: 27°C  |
| Evaporation rate                             | : Not available.  |
| Flammability (solid, gas)                    | : Not available.  |
| Upper/lower flammability or explosive limits | : Greatest known range: Lower: 1.4% Upper: 7.6% (n-butyl acetate)   |
| Vapour pressure                              | : Not available.  |
| Vapour density                               | : Highest known value: 4.6 (Air = 1) (2-methoxy-1-methylethyl acetate).<br>Weighted average: 4.04 (Air = 1) |
| Relative density                             | : 1.03  |
| Solubility(ies)                              | : Not available.  |
| Partition coefficient: n-octanol/ water      | : Not available.  |
| Auto-ignition temperature                    | : Not available.  |
| Decomposition temperature                    | : Not available.  |
| Viscosity                                    | : Kinematic (room temperature): 2.25 cm <sup>2</sup> /s   |
| Explosive properties                         | : Not available.  |
| Oxidising properties                         | : Not available.  |

### 9.2 Other information

No additional information.

## SECTION 10: Stability and reactivity

|   |  |
|---|--|
| 10.1 Reactivity                         | : No specific test data related to reactivity available for this product or its ingredients.                                     |
| 10.2 Chemical stability                 | : Stable under recommended storage and handling conditions (see Section 7).  |
| 10.3 Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur.  |
| 10.4 Conditions to avoid                | : When exposed to high temperatures may produce hazardous decomposition products.  |
| 10.5 Incompatible materials             | : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids. |
| 10.6 Hazardous decomposition products   | : Under normal conditions of storage and use, hazardous decomposition products should not be produced.                           |



## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

#### Acute toxicity

| Product/ingredient name                  | Result                 | Species | Dose         | Exposure |
|--|------------------------|---------|--------------|----------|
| n-butyl acetate                          | LC50 Inhalation Vapour | Rat     | 390 ppm      | 4 hours  |
|  | LD50 Dermal            | Rabbit  | >17600 mg/kg | -        |
|  | LD50 Oral              | Rat     | 10768 mg/kg  | -        |
| heptan-2-one                             | LD50 Oral              | Rat     | 1600 mg/kg   | -        |
|  | LD50 Oral              | Rat     | 8400 mg/kg   | -        |
| Solvent naphtha (petroleum), light arom. | LD50 Oral              | Rat     | 8400 mg/kg   | -        |
|  | LD50 Oral              | Rat     | 8400 mg/kg   | -        |
| 2-methoxy-1-methylethyl acetate          | LD50 Dermal            | Rabbit  | >5 g/kg      | -        |
|  | LD50 Oral              | Rat     | 8532 mg/kg   | -        |
| 1,2,4-trimethylbenzene                   | LD50 Oral              | Rat     | 8532 mg/kg   | -        |
|  | LD50 Oral              | Rat     | 5 g/kg       | -        |

**Conclusion/Summary** : Not available.

#### Acute toxicity estimates

| Route                | ATE value     |
|----------------------|---------------|
| Oral                 | 27700.9 mg/kg |
| Inhalation (vapours) | 160.2 mg/l    |

#### Irritation/Corrosion

| Product/ingredient name                  | Result                   | Species | Score | Exposure                 | Observation |
|--|--------------------------|---------|-------|--------------------------|-------------|
| n-butyl acetate                          | Eyes - Moderate irritant | Rabbit  | -     | 100 milligrams           | -           |
|  | Skin - Moderate irritant | Rabbit  | -     | 24 hours 500 milligrams  | -           |
| heptan-2-one                             | Skin - Mild irritant     | Rabbit  | -     | 24 hours 14 milligrams   | -           |
|  | Skin - Mild irritant     | Rabbit  | -     | 24 hours 100 microliters | -           |
| Solvent naphtha (petroleum), light arom. | Eyes - Mild irritant     | Rabbit  | -     | 24 hours 100 microliters | -           |

**Conclusion/Summary** : Not available.

#### Sensitisation

**Conclusion/Summary** : Not available.

#### Mutagenicity

**Conclusion/Summary** : Not available.

#### Carcinogenicity

**Conclusion/Summary** : Not available.

## SECTION 11: Toxicological information

### Reproductive toxicity

Conclusion/Summary : Not available.

### Teratogenicity

Conclusion/Summary : Not available.

### Specific target organ toxicity (single exposure)

| Product/ingredient name                   | Category                 | Route of exposure                  | Target organs                                    |
|---|--------------------------|------------------------------------|--|
| n-butyl acetate<br>1,2,4-trimethylbenzene | Category 3<br>Category 3 | Not applicable.<br>Not applicable. | Narcotic effects<br>Respiratory tract irritation |

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

| Product/ingredient name                  | Result                         |
|--|--------------------------------|
| Solvent naphtha (petroleum), light arom. | ASPIRATION HAZARD - Category 1 |

Other information : Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

There are no data available on the mixture itself.  
 Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

| Product/ingredient name | Result   | Species   | Exposure             |
|-------------------------|--|---|----------------------|
| n-butyl acetate         | Acute LC50 32000 µg/l Marine water                                       | Crustaceans - Artemia salina - Nauplii                                | 48 hours             |
| heptan-2-one            | Acute LC50 62000 µg/l<br>Acute LC50 131000 to 137000 µg/l<br>Fresh water | Fish - Danio rerio<br>Fish - Pimephales promelas                      | 96 hours<br>96 hours |
| 1,2,4-trimethylbenzene  | Acute LC50 4910 µg/l Marine water<br>Acute LC50 22.4 mg/l Fresh water    | Crustaceans - Elasmopus pecteniscrus - Adult<br>Fish - Tilapia zillii | 48 hours<br>96 hours |

Conclusion/Summary : Not available.

### 12.2 Persistence and degradability

Conclusion/Summary : Not available.

### 12.3 Bioaccumulative potential

| Product/ingredient name                  | LogP <sub>ow</sub> | BCF        | Potential |
|--|--------------------|------------|-----------|
| n-butyl acetate                          | 2.3                | -          | low       |
| heptan-2-one                             | 2.26               | -          | low       |
| Solvent naphtha (petroleum), light arom. | -                  | 10 to 2500 | high      |
| 2-methoxy-1-methylethyl acetate          | 1.2                | -          | low       |
| 1,2,4-trimethylbenzene                   | 3.63               | 243        | low       |

## SECTION 12: Ecological information

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

**PBT** : Not applicable.

**vPvB** : Not applicable.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

**Disposal considerations** : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

#### European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

| Waste code | Waste designation   |
|------------|---|
| 08 01 11*  | waste paint and varnish containing organic solvents or other hazardous substances |

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.




**Disposal considerations** : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

| Type of packaging     | European waste catalogue (EWC)  |
|-----------------------|---|
| CEPE Paint Guidelines | 15 01 10*<br>packaging containing residues of or contaminated by hazardous substances |

## SECTION 13: Disposal considerations

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spill material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

|                            | ADR/RID  | IMDG   | IATA   |
|----------------------------|--|--|--|
| UN number                  | UN1263   | UN1263   | UN1263   |
| UN proper shipping name    | PAINT  | PAINT  | PAINT  |
| Transport hazard class(es) | 3<br> | 3<br> | 3<br> |
| Packing group              | III  | III  | III  |
| Environmental hazards      | No.  | No.  | No.  |
| Additional information     | <b>Special provisions</b><br>640 (E)<br><br><b>Tunnel code</b><br>(D/E)                | F-E, _S-E_<br>-  | -  |

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** : Not applicable.

## SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU Regulation (EC) No. 1907/2006 (REACH)**

**Annex XIV - List of substances subject to authorisation**

**Annex XIV**

None of the components are listed.

**Substances of very high concern**

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

## SECTION 15: Regulatory information

### Other EU regulations

**VOC** : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

**VOC for Ready-for-Use Mixture** : Not applicable.

### Seveso II Directive

This product is controlled under the Seveso Directive.

### Danger criteria

| Category   |
|--|
| P5c: Flammable liquids 2 and 3 not falling under P5a or P5b<br>C6: Flammable (R10) |

### National regulations

**Industrial use** : The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol (Annexes A, B, C, E)

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Inform Consent (PIC)

Not listed.

#### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

**15.2 Chemical safety assessment** : No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

**CEPE code** : 1

Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** : ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

## SECTION 16: Other information

| Classification   | Justification   |
|--|---|
| Flam. Liq. 3, H226<br>STOT SE 3, H336<br>Aquatic Chronic 3, H412 | On basis of test data<br>Calculation method<br>Calculation method |

|  |  |   |
|--|--|---|
| <b>Full text of abbreviated H statements</b> | : H226<br>H302 (oral)<br>H304<br>H315<br>H319<br>H332 (inhalation)<br>H335<br>H336<br>H411<br>H412 | Flammable liquid and vapour.<br>Harmful if swallowed.<br>May be fatal if swallowed and enters airways.<br>Causes skin irritation.<br>Causes serious eye irritation.<br>Harmful if inhaled.<br>May cause respiratory irritation.<br>May cause drowsiness or dizziness.<br>Toxic to aquatic life with long lasting effects.<br>Harmful to aquatic life with long lasting effects. |
|--|--|---|

|   |  |  |
|---|--|--|
| <b>Full text of classifications [CLP/GHS]</b> | : Acute Tox. 4, H302<br>Acute Tox. 4, H332<br>Aquatic Chronic 2, H411<br>Aquatic Chronic 3, H412<br>Asp. Tox. 1, H304<br>EUH066<br>Eye Irrit. 2, H319<br><br>Flam. Liq. 3, H226<br>Skin Irrit. 2, H315<br>STOT SE 3, H335<br><br>STOT SE 3, H336 | ACUTE TOXICITY (oral) - Category 4<br>ACUTE TOXICITY (inhalation) - Category 4<br>LONG-TERM AQUATIC HAZARD - Category 2<br>LONG-TERM AQUATIC HAZARD - Category 3<br>ASPIRATION HAZARD - Category 1<br>Repeated exposure may cause skin dryness or cracking.<br>SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2<br><br>FLAMMABLE LIQUIDS - Category 3<br>SKIN CORROSION/IRRITATION - Category 2<br>SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3<br>SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 |
|---|--|--|

**Date of printing** : 10/24/2016.

**Date of issue/ Date of revision** : 10/24/2016.

**Date of previous issue** : 10/14/2016.

**Version** : 1

### Notice to reader

#### **FOR PROFESSIONAL USE ONLY**

**IMPORTANT NOTE** The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

#### **Head Office**

International Paint Ltd., Stonegate Ln, Gateshead NE10 OJY, United Kingdom. [www.akzonobel.com/yacht](http://www.akzonobel.com/yacht)